

- Can be powered by a 6V vehicle adapter or a wall power outlet
- Memory for 16 different calibrations
- Provides consistency when running samples
- Eliminates pre-weighing with an internal scale
- Preloaded with 10 languages
- Printer connection capabilities





GAC™ 500XT

Grain Moisture Tester

Unbeatable Accuracy

Whether you're harvesting or drying, precision moisture testing is key. For accuracy you can't beat, choose the GACTM 500XT moisture tester.



Measurement MethodCapacitance, conductance, internal scaleMoisture Range5-45% (depending on nut calibrations)

Temperature Compensation Automatic **Moisture Resolution** 0.1% moisture

Sample Size 250 gr. (approx. for cereal grains)

Display LCD (128 x 64 pixels) **Approximate Dimensions** 13.5" H x 10.3" W x 13.8" D

(34,5 cm H x 26,5 cm W x 35,0 cm D)

Approximate Weight 13 lbs. (5.78 kg)

Calibrations 16 pre-loaded calibrations

Installation Requirements

Operating Temperature

Humidity

Power Supply

41 – 113° F (5 – 45° C)

5 – 95% non-condensing

Wall mount adapter, 90-264 VAC, 47-63 Hz, 0.4A max 6-volt vehicle

adapter, 12-24 VDC

Backed by the power of DICKEY-john®:

When you buy a GACTM 500XT you get all the dependability and value you expect from DICKEY-john® products. DICKEY-john's advanced technology and superior electronics are backed by a team of expert, in-house mechanical, electrical, software, and test engineers. Made in the U.S.A.





Easy to Use Display



Pull Slide to Test Grain



Release Lever to Dump Grain

